



# 不銹鋼配管

PQ



1 不銹鋼配管



2 立布

不銹鋼配管											
稱呼	外徑mm	厚度mm	每公尺價格	稱呼	外徑mm	厚度mm	每公尺價格				
1/8	10.5	1.2	48	4	114.3	2.0	676				
		1.5	60			2.5	826				
1/4	13.8	1.2	59			3.0	969				
		1.5	73			3.5	1206				
		1.5	93			4.0	1316				
3/8	17.3	2.0	110			5.0	1750				
		2.0	112			6.0	2080				
1/2	20.4	2.5	133			5	139.8	2.5	1065		
		2.0	120					3.0	1250		
1/2	21.7	2.5	143					3.5	1530		
		2.0	151					4.0	1680		
3/4	27.2	2.5	182					5.0	2265		
		2.0	195	6.0	2695						
1	34.0	2.5	236	6	165.2			3.0	1485		
		3.0	274					3.5	1815		
		3.5	332					4.0	1990		
		4.0	361					5.0	2690		
		2.0	248					6.0	3205		
1 1/4	42.7	2.5	300					8	216.3	3.0	1970
		3.0	350			3.5	2410				
		3.5	427			4.0	2645				
		4.0	465			5.0	3545				
		2.0	281			6.0	4235				
1 1/2	48.6	2.5	341			10	267.4			3.0	2645
		3.0	398							3.5	3240
		3.5	491	4.0	3560						
		4.0	536	5.0	4605						
		2.0	353	6.0	5505						
2	60.5	2.5	429	12	318.5					3.0	3155
		3.0	501							3.5	3870
		3.5	621					4.0	4250		
		4.0	679					5.0	5500		
		2.0	447					6.0	6580		
2 1/2	76.3	2.5	545					14	355.6		
		3.0	638							16	406.4
		3.5	792			18	457.2				
		4.0	862			20	508.0				
		5.0	1185			22	558.8				
3	89.1	2.0	523			24	609.6				
		2.5	638							26	660.4
		3.0	748	28	711.2						
		3.5	930	30	762.0						
		4.0	1014	32	812.8						
		5.0	1395	34	863.6						
		5.5	1470	36	914.4						
3 1/2	101.6	2.0	600	40	1016.0						
		2.5	732					42	1066.8		
		3.0	858								
		3.5	1068								
		4.0	1165								
		5.0	1550								

外徑最高可訂製至80"  
拋光費用另計

一般配管用不銹鋼管(壓接管)							
稱呼	外徑mm	厚度mm	每公尺價格	稱呼	外徑mm	厚度mm	每公尺價格
10	12.70	0.8		75	76.3	1.5	965
13	15.88	0.8	116	80	89.1	2.0	
	20.40	1.0	4M實價	100	114.3	2.0	
20	22.22	1.0	189	125	139.8	2.0	
25	28.58	1.0	246	150	165.2	3.0	
30	34.00	1.2	343	200	216.3	3.0	
40	42.70	1.2	434	250	267.4	3.0	
50	48.60	1.2	497	300	318.5	3.0	
60	60.50	1.5	762				

ASTM A778 · ASTM A312 · ASTM A358						
稱呼外徑		厚度	SCH 5S	SCH 10S	SCH 40S	SCH 80S
outside diameter	外徑mm					
NB	NPS	mm	mm	mm	mm	mm
8	1/4"	13.72		1.65	2.24	3.02
10	3/8"	17.15		1.65	2.31	3.20
15	1/2"	21.34	1.65	2.11	2.77	3.73
20	3/4"	26.67	1.65	2.11	2.87	3.91
25	1"	33.40	1.65	2.77	3.38	4.55
32	1 1/4"	42.16	1.65	2.77	3.56	4.85
40	1 1/2"	48.26	1.65	2.77	3.68	5.08
50	2"	60.33	1.65	2.77	3.91	5.54
65	2 1/2"	73.03	2.11	3.05	5.16	7.01
80	3"	88.90	2.11	3.05	5.49	7.62
90	3 1/2"	101.60	2.11	3.05	5.74	8.08
100	4"	114.30	2.11	3.05	6.02	8.56
125	5"	141.30	2.77	3.40	6.55	9.52
150	6"	168.28	2.77	3.40	7.11	10.97
200	8"	219.08	2.77	3.76	8.18	12.70
250	10"	273.05	3.40	4.19	9.27	12.70
300	12"	323.85	3.96	4.57	9.52	12.70

· CNS 6331 G3124 · JIS G3459							
稱呼外徑		厚度	SCH 5S	SCH 10S	SCH 20S	SCH 40S	SCH 80S
outside diameter	外徑mm						
(A)	(B)	mm	mm	mm	mm	mm	mm
8	1/4"	13.8	1.2	1.65	2.0	2.2	3.0
10	3/8"	17.3	1.2	1.65	2.0	2.3	3.2
15	1/2"	*21.7	1.65	2.1	2.5	2.8	3.7
20	3/4"	*27.2	1.65	2.1	2.5	2.9	3.9
25	1"	*34.0	1.65	2.8	3.0	3.4	4.5
32	1 1/4"	42.7	1.65	2.8	3.0	3.6	4.9
40	1 1/2"	48.6	1.65	2.8	3.0	3.7	5.1
50	2"	60.5	1.65	2.8	3.5	3.9	5.5
65	2 1/2"	76.3	2.1	3.0	3.5	5.2	7.0
80	3"	89.1	2.1	3.0	4.0	5.5	7.6
90	3 1/2"	101.6	2.1	3.0	4.0	5.7	8.1
100	4"	114.3	2.1	3.0	4.0	6.0	8.6
125	5"	139.8	2.8	3.4	5.0	6.6	9.5
150	6"	165.2	2.8	3.4	5.0	7.1	11.0
200	8"	216.3	2.8	4.0	6.5	8.2	12.7
250	10"	267.4	3.4	4.0	6.5	9.3	15.1
300	12"	318.5	4.0	4.5	6.5	10.3	17.4

一般配管(壓接管):水電明管配裝用。  
工業配管:石化、瓦斯、自來水、污水處理、釀酒、蒸氣、  
下水道工程...等。

\* 國內建築、水電用配管: 外徑1/2"為20.0mm, 厚度2.0~2.5mm  
外徑3/4"為26.0mm, 厚度2.0~2.5mm  
外徑1"為33.0mm, 厚度2.0~3.0mm

# 不銹鋼被覆管

PURZ、PQZ



① 被覆管

PE發泡被覆不銹鋼壓接管

外徑 (mm)	尺寸	鋼管厚度 (mm)	E.SUN-01(明管)		E. SUN-02(暗管)		E.SUN-03(冷水管)	
			被覆厚度	牌價/米	被覆厚度	牌價/米	被覆厚度	牌價/米
15.88	1/2"	0.8	6.0	280	2.6	160	0.8	110
20.40		1.0		實價		實價		
22.22	3/4"	1.0	6.0	420	3.3	260	0.8	180
28.58	1"	1.0	6.0	530	4.5	380	0.8	240
34.00	1 1/4"	1.2	7.0	980	7.0	560	0.8	390
42.70	1 1/2"	1.2	8.0	1230	8.0	700	0.8	490
48.60	2"	1.2	9.0	1450	9.0	840	0.8	590
60.50	2 1/2"	1.5	9.0	2030	10.0	1160	0.8	810

PE發泡被覆不銹鋼配管

尺寸	鋼管厚度 (mm)	E.SUN-11(明管)		E. SUN-12(暗管)		E.SUN-13(冷水管)	
		被覆厚度	牌價/米	被覆厚度	牌價/米	被覆厚度	牌價/米
1/2"	2.5	6.0	520	2.6	280	0.8	210
3/4"	2.5	6.0	660	3.3	400	0.8	300
1"	3.0	6.0	1080	4.5	600	0.8	450
1 1/4"	3.0	8.0	1400	7.0	1040	0.8	780
1 1/2"	3.0	9.0	1640	8.0	1220	0.8	910
2"	3.0	9.0	2080	9.0	1550	0.8	1160
2 1/2"	3.0	10.0	2850	9.0	2120	0.8	1580
3"	3.0	10.0	3990	10.0	2970	0.8	2220
4"	3.0	10.0	6060	10.0	4510	0.8	3380

不銹鋼配管—不銹鋼被覆管